



5  
Year Warranty

IP65

IK08

Photocell

✓ IES Files

Double Insulated


Photocell

CPRIS

**Eterna**  
Everyday Lighting For Professionals

**12W IP65 CIRCULAR LED  
FITTING WITH PHOTOCELL**

- Polycarbonate diffuser
- One rear and four side 20mm entries
- Push fit terminal block
- Stainless steel captive fixing screws
- Photocell for dusk to dawn operation



Code	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
CO12SCPC	12W	4200K	1200 lm	35,000 hrs	IP65 IK08	1 / 10
CPRIS	Prismatic Diffuser					1 / 50

**LED LAMP SPECIFICATIONS:**

Luminaire lumens (with diffuser)	<b>1200 lm</b>
Lumens from chip (no diffuser)	<b>1450 lm</b>
Useful lumens	<b>1150 lm</b>
Rated Wattage	12W
Rated luminous flux	1150 lm
Nominal life time of the lamp	35,000 hrs
Colour temperature	4200K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60% of the full light output	<1s
Dimmable	No
Nominal beam angle	120°
Rated power	12W
Rated lamp lifetime	35,000 hrs
Lamp power factor	>0.9
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	280cd
Rated beam angle	120°
Voltage / Frequency	240V~50-60Hz
Not suitable for accent lighting	