



**LV SURFACE/RECESSED CAPSULE DOWNLIGHTS**

These low voltage downlights provide attractive and modern housing for low voltage light sources.

- Requires 1 x suitable 20W 12V G4 M47 halogen capsule (included). Fitting is rated at 20W max
  - This luminaire is compatible with bulbs of the energy classes: B to E and is sold with a bulb of the energy class: B
  - Pressed steel construction
  - Pre-wired with mini connector and 2.4 metres of silicone cable: easy installation with plug in system, or can be direct wired by removing mini connector
  - Frosted glass diffuser: soft lighting effect
  - Compatible with 5 way manifold block fitted on D034 transformer: flexible installation options
  - Can be surface or recessed mounted
  - Recessed hole cut out size: 61mm
- M.O.M: 3 / O.P.Q: 60

Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
D041	Polished Chrome	20W	2700K	300 lm	2,000 hrs	IP20	B
D042	Brushed Nickel						
D043	White						
D045	Satin Brass						

**Eterna** D041-45

**B**

21.2 kWh/1000h

**Eterna** D041-45

This luminaire is compatible with bulbs of the energy classes:

This luminaire is sold with a bulb of the energy class: **B**

874/2012

**LAMP SPECIFICATIONS:**

Lumens total flux	<b>300 lm</b>
Lumens 120° flux	<b>260 lm</b>
Rated Wattage	20W
Rated luminous flux	260 lm
Nominal life time of the lamp	2,000 hrs
Colour temperature	2700K
Number of switching cycles before premature lamp failure	10,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	Yes
Lamp dimensions (mm)	28 x 10
Nominal beam angle	<120°
Rated power	20W
Rated lamp lifetime	2,000
Lamp power factor	1
Lumen maintenance factor at end of nominal life	70%
Starting time	0.2s
Colour rendering	100%
Rated peak intensity	320cd
Rated beam angle	<120°