


LED DECORATIVE OVER **MIRROR LIGHT**

- Multiple low power LED array
- Pull cord on/off switch
- Steel body
- Polycarbonate diffuser



Code	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
OML12LED	Polished Chrome	12W	3000K	880 lm	20,000 hrs	IP44	А

EternaPro • M.O.M: 1 / O.P.Q: 8 **LED** 5 YEAR Warranty*

Eterna	OML12LED			
	ıminaire ns built-in mps.			
A ⁺ A C D	}L E D			
The lamps cannot be changed in the luminaire.				
874/2012	$ \bigcirc $			

0.4202			
LED LAMP SPECIFICATION	IS:		
Luminaire lumens (with diffuser)	880 lm		
Lumens from chip (no diffuser)	1230 lm		
Useful lumens	810 lm		
Rated Wattage	12W		
Rated luminous flux	810 lm		
Nominal life time of the lamp	20,000 hrs		
Colour temperature	3000K		
Number of switching cycles before premature lamp failure	10,000		
Warm-up time up to 60% of the full light output	Instant full light		
Dimmable	No		
LED array dimensions (L/W)	288x42mm		
Nominal beam angle	120°		
Rated power	12W		
Rated lamp lifetime	20,000 hrs		
Lamp power factor	0.83		
Lumen maintenance factor at end of nominal life	70%		
Starting time	<0.5		
Colour rendering	>80		
Colour consistency	Within a six step Macadam ellipse		
Rated peak intensity	246cd		
Rated beam angle	120°		
Voltage / Frequency	240V~50Hz		
Not suitable for acce	nt lighting		