

Type of Light source

| | |
|---|------|
| Lighting Technology used | LED |
| Non-Directional or Directional | NDLS |
| Light Source Cap type (or other interface) | N/A |
| Mains or non-mains | MLS |
| Connected Light source (CLS) | No |
| Colour tuneable light source | No |
| High Luminance Light source | No |
| Anti Glare shield | No |
| Dimmable (Dimmers listed in Product File if applicable) | No |

Product Parameters

| | |
|---|------------|
| Energy consumption kW/1000hrs (enter wattage / On Mode Power) | 15.6 |
| Energy Efficiency Class | E |
| Useful Luminous Flux (lumens) | 2085 |
| Beam angle correspondence | Wide Cone |
| Correlated Colour temperature (K) | 3000 |
| Correlated Colour temperature (range to) | 40,006,000 |
| On-mode Power (W) | 15.6 |
| Standby Power | 0 |
| Networked Standby Power | 0 |
| Colour Rendering Index | 86.7 |
| Colour Rendering Index Range | 84.4,86.3 |
| Dimensions Height | 74 |
| Dimensions width | 185 |
| Dimensions depth | 275 |
| Chromaticity coordinates x | 0.4305 |
| Chromaticity coordinates y | 0.3953 |

Parameters for Directional Light Sources

| | |
|------------------------------------|-----|
| Peak Luminous Intensity (cd) | 385 |
| Beam Angle (degrees) | 120 |
| Beam Angle range minimum (degrees) | |
| Beam Angle range maximum (degrees) | |

Parameters for Led & OLED sources

| | |
|----------------------------|-----|
| R9 Colour rendering Index | 17 |
| Survival Factor | 0.9 |
| Lumens maintainance factor | 0.9 |

Parameters for Led & OLED mains sources

| | |
|--|---------|
| Displacement Factor | 0.92 |
| Colour Consistency in SDCM Steps | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage Replacement claim (W) | N/A |
| Flicker Metric | 0.5 |
| Stroboscopic Effect Metric | 0.013 |
| Spectrum Report available | Yes |
| EPREL Registration | 1253140 |