



LED EMERGENCY TWINSPOT

Twin 3W | 3500K | 441 lm | 30,000 hrs | IP65

- Replacement battery code: EB3 • 5 year warranty
- Minimum 3 hour non-maintained functionality in emergency mode
- Horizontally and vertically adjustable heads, 180° rotation across the horizontal plane



1

Code	Version
LEDTWNSPOT	Standard
SELTWNSPOT	Self-Test

LED SLIM WALL PACKS

17W | 3000/4000/6000K | 36,000 hrs | IP65

- Colour temperature selectable - easily set by a dip switch on the driver • Up to 90 lm / W
- 5 year warranty • ABS base, opal diffuser
- 20mm cable entries on either side and one to the rear



2

Code	Version
WPCSBK	Black
WPCSWH	White
WPCSBKPC	Black Photocell
WPCSWHPC	White Photocell

LED CIRCULAR HIGH BAYS

IP65

- Aluminium housing, glass lens cover
- IK08 rated durable construction
- 1-10V dimmable capability as standard
- 80cm stainless steel safety cable attached
- Supplied with mains input cable and 1-10V cable
- IES files available
- 5 year warranty

3



Code	Version
HBCIR100	100W / 4000K / 14850 lm / 30,000 hrs
HBCIR150PP	150W / 3500K / 25400 lm / 50,000 hrs
HBCIRDIF90	90° aluminium reflector

LED LINEAR HIGH BAY

150W | 6300K | 21460 lm | 40,000 hrs | IP20

Long life, high performance luminaire offering low energy consumption and high lumen output at 143 lumens per watt. For use in racked areas of warehouses or many other applications such as manufacturing, leisure facilities and retail environments.

- Aluminium housing, polycarbonate lens cover
- Supplied with 1.5m mains cable
- Includes adjustable hanging kit (1.5m length)
- Includes ceiling/wall tilt brackets • 5 year warranty



4

Code
HBAYLIN

LED 150W CIRCULAR HIGH BAY

150W | 4000K | 18500 lm | 30,000 hrs | IP65

- Aluminium housing, polycarbonate lens cover
- IK09 rated durable construction • 5 year warranty
- 1-10V dimmable capability as standard
- Meanwell driver, Philips Lumileds LED chips
- Supplied with 30cm mains input cable and 30cm 1-10V cable • IES files available • 120 lm / W



5

Code	Version
HBAYLEDICIR	Fitting
HBDIFALU90	90° aluminium reflector
HBDIFPC60	60° Polycarbonate Reflector

LED LOW BAY FITTINGS

4000K | 35,000 hrs | IP40

- Frosted polycarbonate diffuser & aluminum housing
- Suspension pack included, max length 1.5m
- Brackets available separately (see LBB range) for surface mounting or to enable installation with threaded rod
- Fitted with 1.5m mains input cable • >100 lm / W
- 5 year warranty



6

Code	Version
LEDLBAY30	30W / 3050 lm
LEDLBAY50	50W / 5100 lm
LEDLBAY80	80W / 8150 lm
LEDLBAY120	120W / 12200 lm

LED BATTENS

4200K | 35,000 hrs | IP20

- LED tray can be removed from the housing for easy installation
- 20mm knockout glands at each end for through wiring options
- Gear tray retaining straps
- Push terminal connections
- BESA box mounting
- 5 year warranty

7



Code	Version
BATLED4FT	4ft / 23W / 2950 lm
BATLED4FT	5ft / 38W / 4750 lm
BATLED4FT	6ft / 48W / 6050 lm
BATLEDPIR	Add-on PIR Sensor



Emergency & high output versions also available

LED HIGH OUTPUT FLOODLIGHTS

4000K | 25,000 hrs | IP65

- High Power LED Chip array: which is better suited to these higher power ratings, where the large physical size of the housing and chip array maximises performance
- available from this technology
- Over 108 Lumens per circuit Watt
- Die cast aluminium construction, toughened safety glass lens
- Pre-wired with 80cm of cable
- 5 year warranty

8



Code	Version
FLOOD50W	50W / 5400 lm
FLOOD80W	80W / 9400 lm
FLOOD120W	120W / 14500 lm
FLOOD200W	200W / 23000 lm

Bracket can be removed from fitting for easy installation

