

## **Product Information Sheet**

Product Code

600P4K

Type of Light source			
Lighting Technology used	LED	LED	
Non-Directional or Direction	Non-Directional		
Light Source Cap type (or o	N/A		
Mains or non-mains	Mains		
Connected Light source (CL	No		
Colour tuneable light source	No		
High Luminance Light source		No	
Anti Glare shield	No		
Dimmable	(Dimmers listed in Product Fi		
Product Parameters	(		
Energy consumption	kW/1000hrs (enter wattage	/ On Mode Power) 36	
Energy Efficiency Class	F		
Useful Luminous Flux (lume	4300		
Beam angle correspondence	Wide Cone 120°		
Correlated Colour tempera	Single Value		
Correlated Colour tempera	4000		
On-mode Power (W)	ture (K)	36	
` '	0		
Standby Power Networked Standby Power	0		
·	83.3		
Colour Rendering Index	83.3		
Colour Rendering Index Ra	-	25	
Dimensions	Height	25	
Dimensions	width	595	
Dimensions	depth	595	
Chromaticity coordinates x		0.3726	
Chromaticity coordinates y		0.3739	
Parameters for Directional		N/A	
Peak Luminous Intensity (c	a)	N/A	
Beam Angle (degrees)	N/A		
Beam Angle range minimu			
Beam Angle range maximu			
Parameters for Led & OLEI	) sources		
R9 Colour rendering Index		7	
Survival Factor		0.9	
Lumens maintainance factor		0.8	
Parameters for Led & OLE	O mains sources		
Displacement Factor		1	
Colour Consistency in	SDCM Steps	6	
_	urce replaces a fluorescent ligh		
without integrated ballast of a particular wattage			
Replacement	: claim (W)	N/A	
Flicker Metric	Pst	0.1	
Stroboscopic Effect Metric	SVM	0.1	
Stroboscopic Effect Wethe	34141	U.1	
Spectrum Report available	Yes		
50051 D		769269	
FUREI Redictration	EPREL Registration		