


## **800 LUMEN A SHAPE LED LAMPS**

Opal envelope: gives excellent all round illumination with soft appearance

Fantastic energy saving & reliable alternative to conventional incandescent versions


- 15,000 hours average life expectancy: much reduced lamp replacement cycle & maintenance
- Flicker free instant start
- Non dimmable
- Non annihole
- M.O.M: 1 / O.P.Q: 10

| Code      | Wattage | Сар<br>Туре | Colour<br>Temp. | Lumens | Avg. Rated<br>Life (Hrs) | Energy<br>Rating |
|-----------|---------|-------------|-----------------|--------|--------------------------|------------------|
| ALED800ES | 9W      | ES (E27)    | 2700K           | 800 lm | 15,000 hrs               | A+               |
| ALED800BC |         | BC (B22)    |                 |        |                          |                  |









| LED LAMP SPECIFICATIONS:                                       |                                  |  |  |  |  |
|--|----------------------------------|--|--|--|--|
| Nominal luminous flux  | 800 lm                           |  |  |  |  |
| Rated Wattage  | 9W                               |  |  |  |  |
| Rated luminous flux  | 800 lm                           |  |  |  |  |
| Nominal life time of the lamp                                  | 15,000 hrs                       |  |  |  |  |
| Colour temperature   | 2700K                            |  |  |  |  |
| Number of switching cycles<br>before premature lamp<br>failure | >7500                            |  |  |  |  |
| Warm-up time up to 60 % of the full light output               | Instant full light               |  |  |  |  |
| Dimmable   | No                               |  |  |  |  |
| Lamp dimensions (L/Ø)  | 110 x 60mm                       |  |  |  |  |
| Rated power  | 9W                               |  |  |  |  |
| Rated lamp lifetime  | 15,000 hrs                       |  |  |  |  |
| Lamp power factor  | 0.5                              |  |  |  |  |
| Lumen maintenance factor at end of nominal life                | 70%                              |  |  |  |  |
| Starting time  | <0.5s                            |  |  |  |  |
| Colour rendering   | >80                              |  |  |  |  |
| Colour consistency   | Within 6 step<br>Macadam ellipse |  |  |  |  |
| Cap type   | ES / BC                          |  |  |  |  |
| Voltage / Frequency  | 240V~50Hz                        |  |  |  |  |