CATALOGUE RANGE: Ceiling/Wall/Bulkheads

✓ Lighting design service available

Year Warranty

IP65

Double Insulated 0 Hole Knockouts



450 lm Lumens total flux 405 lm Lumens 120° flux 6W Rated Wattage Rated luminous flux 450 lm Nominal life time of the lamp 25,000 hrs Colour temperature 4200K Number of switching cycles before premature lamp ≥15,000 failure Warm-up time up to 60 % of Instant full light the full light output Dimmable No Lamp dimensions (L/W) 110 x 42mm Nominal beam angle 120° Rated power 6W Rated lamp lifetime 25,000 hrs Displacement factor 0.98 Lumen maintenance factor at ≥0.70 end of nominal life Starting time <0.1s Colour rendering ≥80 Within 6 step Colour consistency Macadam ellipse Rated peak intensity 160cd

Not suitable for accent lighting

120°

240V

design utility bulkhead

- Instant start to full illumination level: giving crisp, super bright light output
- Polycarbonate construction: impact and corrosion resistant
- External fixing points: for quick & easy installation
- 3 x 20mm cable entries: offering multiple installation options
- Compact design

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
ATOM5	6W	4200K	450 lm	25,000 hrs	IP65	1 / 20

