



- Steel construction
- Visually similar to 20W G4 halogen
- 3000K warm colour temperature: offering a pleasing lighting appearance
- 1.7W = 160 lumens: ideal low energy solution to standard halogen cabinet lights
- Not suitable for use with dimmers
- Pre-wired with 2m mains cable and no separate driver required: facilitating easy installation
- Mains voltage: integral driver



Lumens total flux	<b>160 lm</b>
Lumens 90° flux	<b>150 lm</b>
Rated Wattage	1.7W
Rated luminous flux	150 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	3000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Lamp dimensions (Ø)	41mm
Nominal beam angle	90°
Rated power	1.7W
Rated lamp lifetime	30,000 hrs
Displacement factor	0.95
Lumen maintenance factor at end of nominal life	>70%
Starting time	<0.5s
Colour rendering	>80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	48.2cd
Rated beam angle	90°
Voltage	240V

This product contains a Light Source of Energy Efficiency Class G

Not suitable for accent lighting

Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Hole Cut Out Size	MOM / OPQ
CLEDCIR	Nickel	1.7W	3000K	160 lm	30,000 hrs	IP20	61mm	1 / 40
CLEDCIRWH	White							

