


DOUBLE TURN D CFL LAMPS

- Glass construction
- Non dimmable
- M.O.M: 1 / O.P.Q: 10

Code	Wattage	Cap Type	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	Energy Rating
D1040EB	10W	G24D-1 2 Pin	4000K	600 lm	10,000 hrs	B
D1840EB	18W	G24D-2 2 Pin		1210 lm		
D2640EB	26W	G24D-3 2 Pin		1720 lm		



LAMP SPECIFICATIONS:	D1040EB	D1840EB	D2640EB
Nominal Wattage	10W	18W	26W
Rated Wattage	10W	18W	26W
Nominal lifetime hours (average rated hours)	10,000 hrs	10,000 hrs	10,000 hrs
Nominal useful luminous flux	600 lm	1210 lm	1720 lm
Rated luminous flux	600 lm	1206 lm	1716 lm
Luminous efficacy (Lm/W) in 50Hz operation	60	67	66
Rated lamp Lumen maintenance	2000hrs: 86% 4000 hrs: 79% 8000 hrs: 76%	2000hrs: 87% 4000 hrs: 79% 8000 hrs: 77%	2000hrs: 87% 4000 hrs: 79% 8000 hrs: 76%
Rated survival factors	2000hrs: 100% 4000 hrs: 90% 8000 hrs: 60%	2000hrs: 100% 4000 hrs: 90% 8000 hrs: 60%	2000hrs: 100% 4000 hrs: 90% 8000 hrs: 60%
Lamp dimensions (L/W)	110mm x 35mm ²	150mm x 35mm ²	170mm x 35mm ²
Cap type	G24D-1 2 Pin	G24D-2 2 Pin	G24D-3 2 Pin
Lamp Mercury content to an accuracy of 0.1mg	≤2.5mg	≤2.5mg	≤2.5mg
Colour rendering index Ra	≥80	≥80	≥80
Colour temperature	4000K	4000K	4000K
Ambient temperature required to achieve maximum luminous flux	25°C	25°C	25°C
Dimmable	No	No	No