

The lamps cannot be changed in the luminaire.

874/2012



**FOCUS LED FLOODLIGHTS / WITH PIR**


Modern, compact, aesthetically pleasing LED floodlights with highly adjustable directional lighting

- **10W:** horizontally and vertically adjustable spotlight
- **20W:** 2 horizontally and vertically, independently adjustable 10W spotlights
- Polycarbonate base with die-cast aluminum spotlight head(s)

**PIR VERSIONS:**

- Time on adjustment: 10 secs - 10 mins
- Lux level adjustments
- 140° detection angle
- 10 metre detection range

- **10W** = M.O.M: 1 / O.P.Q: 12
- **20W** = M.O.M: 1 / O.P.Q: 8



**Eterna**  
**LED**  
**2 YEAR**  
Warranty  
Subject to T&C's

Code	Version	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
FOCUS10	Standard	Grey	10W	4200K	680 lm	25,000 hrs	IP54	A
FOCUS20	Standard	Grey	20W	4200K	1500 lm	25,000 hrs	IP54	A
FOCUS10PIR	140° PIR	Grey	10W	4200K	680 lm	25,000 hrs	IP54	A
FOCUS20PIR	140° PIR	Grey	20W	4200K	1500 lm	25,000 hrs	IP54	A

LAMP SPECIFICATIONS:	10W	20W
Lumens total flux	<b>680 lm</b>	<b>1500 lm</b>
Lumens 90° flux	<b>640 lm</b>	<b>1400 lm</b>
Rated Wattage	10W	20W
Rated luminous flux	680 lm	1360 lm
Nominal life time of the lamp	25,000 hrs	25,000 hrs
Colour temperature	4200K	4200K
Number of switching cycles before premature lamp failure	15,000	15,000
Warm-up time up to 60 % of the full light output	Instant full light	Instant full light
Dimmable	No	No
LED array dimensions (Ø)	29mm	29mm
Nominal beam angle	40°	100°
Rated power	10W	20W
Rated lamp lifetime	25,000 hrs	25,000 hrs
Lamp power factor	>5	>5
Lumen maintenance factor at end of nominal life	70%	70%
Starting time	0.17s	0.34s
Colour rendering	≥65	≥65
Colour consistency	Within 6 step Macadam ellipse	Within 6 step Macadam ellipse
Rated peak intensity	300cd	600cd
Rated beam angle	40°	100°
Voltage	240V	240V