ChannelPlus H27XL Series 2

Electronic programmer

Two channels with 7-day programming and independent timing of heating and hot water. Part of a range of electronic programmers that offer up to four independent channels and feature a large, easy to read display and simple menu driven programming. Three and four channel models are for multiple zone control, with single and two channel models used with combi boiler systems and stored hot water systems.



Applications

- Time control of most domestic gas or oil-fired central heating systems
- · Combi boilers
- Stored HW systems
- Underfloor heating systems
- Zone Control time control of multiple heating zones

Benefits

- Flexible controls
- No need to worry about resetting clock for Summer/ Winter time changes

Features

- · Two channels
- · 7-day programming
- Back-lit LCD display
- Simplified menu driven programming
- Advance and boost on each channel
- Preset clock
- · Automatic Winter/Summer time changes
- 9-pin wall plate
- 7 years no quibbles warranty









ChannelPlus H27XL Series 2



Technical specifications

Electrical

Contact rating 3 (1) Amps 230V AC

Contact type Micro-disconnection Voltage-free (not H37XL)

230V 50 Hz Supply

Environmental

Pollution degree Degree 2 Class a software Type 1 Control

Enclosure protections IP30 Double insulated Yes

0° C to +40 °c Operating temperature range Lithium Battery

Mechanical

Case material Thermoplastic flame retardant

Dimensions 101 x 163 x 37mm

Feautures

Back-lit liquid crystal Display Clock 24-hour or 12-hour am/pm

Displayed time adjustments 1-minute steps Switched time adjustments 10-minute steps

Programme options On, Off, All Day, Auto & Holiday

Operating periods Per-day 3 for each channel

Override (each channel) 1 or 2 hour boost, 1 or 2 hour extension to On period, instant advance

Mounting 9-pin wall fixing plate