




-  LED
-  5 Year Warranty
-  IP65
-  IK08
-  Dimmable
-  ✓ IES Files
-  Earthed



150W CIRULAR HIGH BAY WITH LIFUD DRIVER

- Aluminium housing, glass lens cover
- IK08 rated durable construction
- 1-10V dimmable capability as standard
- Supplied with 42cm mains input cable and 33cm 1-10V cable
- 50cm stainless steel safety cable attached
- Philips Lumileds SMD LEDs • 169 lm/W



LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser)	25400 lm
Lumens from chip (no diffuser)	29000 lm
Useful lumens	21310 lm
Rated Wattage	150W
Rated luminous flux	21310 lm
Nominal life time of the lamp	50,000 hrs
Colour temperature	3500K
Number of switching cycles before premature lamp failure	25,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	Yes
Nominal beam angle	120°
Rated power	150W
Rated lamp lifetime	50,000 hrs
Lamp power factor	>0.9
Lumen maintenance factor at end of nominal life	≥0.80
Starting time	<0.5s
Colour rendering	≥70
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	6994cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Not suitable for accent lighting	

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
HBCIR150PP	150W	3500K	25400 lm	50,000 hrs	IP65 IK08	1 / 1
HBCIRDIF90	90° Aluminium Reflector					1 / 20