



CHANNELPLUS XL SERIES 2 Electronic Programmers

Electronic programmers that offer up to four independent channels and feature a clearly read display and ease of programming.

1, 2, 3 or 4 channels 24 hour or 7 day Back-lit LCD display Preset clock Automatic Winter/Summer time changes Simplified menu driven programming 5 year warranty



Horstmann. Together, we're in control.

Horstmann. Together, we're in control.



CHANNELPLUS H47XL

Programmer with 7 day setting over four independent channels. Designed for use with fully pumped central heating systems using four separate zone valves in addition to many other applications.

CHANNELPLUS H37XL

Programmer with 7 day setting over three independent channels. Designed for use with fully pumped central heating systems using three separate zone valves. Meets zoning requirements of Part L1 of the Building Regulations.

CHANNELPLUS H37VXL

The same as the H37XL but with volt free contacts.

CHANNELPLUS H27ZXL

Two channel with 7 day programming and independent timing of Zone 1 and Zone 2.

CHANNELPLUS H27XL

Two channel with 7 day programming and independent timing of heating and hot water.

CHANNELPLUS H21XL

Two channel with 24 hour programming and independent timing of heating and hot water.

CHANNELPLUS H17XL

Single channel time switch with full 7 day programming.

CHANNELPLUS H11XL

Single channel time switch with 24 hour programming.

Voltage free contacts make both the H11 and H17 units ideal for combi boilers.



Horstmann Controls Limited, South Bristol Business Park, Roman Farm Road, Bristol BS4 1UP. Tel: 0117 978 8700 Fax: 0117 978 8701 E-mail: sales@horstmann.co.uk Web: www.horstmann.co.uk A division of Horstmann Group Ltd. Registered office: PRI House, Moorside Road, Winnall Trading Estate, Winchester, Hampshire S023 7RX. Registered in England No. 457553 ©March 2009: Horstmann Group Ltd: All rights reserved. The company reserves the right to alter product specifications without notice

SPECIFICATION

CONTACT RATING 3 (1) Amps 230V AC CONTACT TYPE Micro-disconnection changeover Voltage free (not H37XL) Type 1 Control SUPPLY 230V 50Hz **OPERATING TEMPERATURE RANGE** 0° C to $+40^{\circ}$ C BATTERY TYPE Lithium CASE MATERIAL Thermoplastic, flame retardent DIMENSIONS 101mm x 163mm x 37mm DISPLAY Back-lit liquid crystal CLOCK 24 hour or 12 hour AM/PM **DISPLAYED TIME ADJUSTMENTS** 1 minute steps SWITCHED TIME ADJUSTMENTS 10 minute steps **PROGRAMME OPTIONS** ON, OFF, All Day, Auto and Holiday **OPERATING PERIODS PER DAY** 3 for each channel OVERRIDE (EACH CHANNEL) 1 or 2 hour boost 1 or 2 hour extension to ON period Instant advance MOUNTING 9 pin wall fixing plate DOUBLE INSULATED Yes **ENCLOSURE PROTECTION** IP 30 POLLUTION DEGREE 2



CHANNELPLU



8

1

P82659 Issue