



**5**  
Year Warranty



✓ IES Files



Earthed



BESA Box  
Compatible



Hole  
Knockouts




Gear tray  
retaining  
chains



**Eterna**<sup>®</sup>  
Everyday Lighting For Professionals

**STANDARD LED BATTENS**

- Pressed steel body and polycarbonate diffuser
- LED tray can be removed from the housing for easy installation
- 20mm knockout glands at each end for through wiring options
- BESA box mounting • Gear tray retaining straps
- Up to 106 lm/W



LED LAMP SPECIFICATIONS:	KBAT4	KBAT5	KBAT6
Luminaire lumens (with diffuser)	<b>1800 lm</b>	<b>2400 lm</b>	<b>3400 lm</b>
Lumens from chip (no diffuser)	<b>2300 lm</b>	<b>2800 lm</b>	<b>4000 lm</b>
Useful lumens	<b>1700 lm</b>	<b>2300 lm</b>	<b>3300 lm</b>
Rated Wattage	18W	24W	32W
Rated luminous flux	1700 lm	2300 lm	3300 lm
Nominal life time of the lamp	30,000 hrs	30,000 hrs	30,000 hrs
Colour temperature	4000K	4000K	4000K
Number of switching cycles before premature lamp failure	15,000	15,000	15,000
Warm-up time up to 60% of the full light output	Instant full light	Instant full light	Instant full light
Dimmable	No	No	No
Nominal beam angle	120°	120°	120°
Rated power	18W	24W	32W
Rated lamp lifetime	30,000 hrs	30,000 hrs	30,000 hrs
Displacement factor	0.94	0.96	0.96
Lumen maintenance factor at end of nominal life	>0.7	>0.7	>0.7
Starting time	<0.1	<0.5	<0.5
Colour rendering	>80	>80	>80
Colour consistency	Within a six step Macadam ellipse	Within a six step Macadam ellipse	Within a six step Macadam ellipse
Rated peak intensity	506cd	624cd	702cd
Rated beam angle	120°	120°	120°
Voltage / Frequency	240V~50Hz	240V~50Hz	240V~50Hz
Lumen efficacy	100 lm / W	100 lm / W	106 lm / W

Code	Length	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
KBAT4	4ft	18W	4000K	1800 lm	30,000 hrs	IP20	1 / 6
KBAT5	5ft	24W		2400 lm			
KBAT6	6ft	32W		3400 lm			

This product contains a Light Source of Energy Efficiency Class E

Not suitable for accent lighting