

| Type of Light source | | |
|--|--|-----------------|
| Lighting Technology used | LED | LED |
| Non-Directional or Directional | | Non-Directional |
| Light Source Cap type (or other interface) | | N/A |
| Mains or non-mains | | Non-Mains |
| Connected Light source (CLS) | | No |
| Colour tuneable light source | | No |
| High Luminance Light source | | No |
| Anti Glare shield | | No |
| Dimmable | (Dimmers listed in Product File if applicable) | No |

| Product Parameters | | |
|------------------------------------|--|----------------|
| Energy consumption | kW/1000hrs (enter wattage / On Mode Power) | 14 |
| Energy Efficiency Class | | D |
| Useful Luminous Flux (lumens) | | 2072 |
| Beam angle correspondence | | Wide Cone 120° |
| Correlated Colour temperature type | | Single Value |
| Correlated Colour temperature (K) | | 4000 |
| On-mode Power (W) | | 14 |
| Standby Power | | 0 |
| Networked Standby Power | | 0 |
| Colour Rendering Index | | 80 |
| Colour Rendering Index Range | | |
| Dimensions | Height | 230 |
| Dimensions | width | 230 |
| Dimensions | depth | 51 |
| Chromaticity coordinates x | | 0.378 |
| Chromaticity coordinates y | | 0.375 |

| Parameters for Directional Light Sources | | |
|---|--|-----|
| Peak Luminous Intensity (cd) | | 432 |
| Beam Angle (degrees) | | 120 |
| Beam Angle range minimum (degrees) | | |
| Beam Angle range maximum (degrees) | | |

| Parameters for Led & OLED sources | | |
|--|--|-----|
| R9 Colour rendering Index | | 6 |
| Survival Factor | | 0.9 |
| Lumens maintainance factor | | 0.9 |

| Parameters for Led & OLED mains sources | | |
|--|------------|---------|
| Displacement Factor | | 0.91 |
| Colour Consistency in | SDCM Steps | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage | | |
| Replacement claim (W) | | |
| Flicker Metric | Pst | 0.1 |
| Stroboscopic Effect Metric | SVM | 0.025 |
| Spectrum Report available | | Yes |
| EPREL Registration | | 1319253 |