




Eterna®
Everyday Lighting For Professionals

| LED LAMP SPECIFICATIONS: | |
|--|-------------------------------|
| Luminaire lumens (with diffuser): Warm White, Cool White, Daylight White | 1560 lm 1670 lm 1600 lm |
| Lumens from chip (array): Warm White, Cool White, Daylight White | 1760 lm 1880 lm 1800 lm |
| Useful lumens (array): Warm White, Cool White, Daylight White | 1400 lm 1500 lm 1440 lm |
| Rated Wattage | 14W |
| Rated luminous flux | 1400/1500/1440 lm |
| Nominal life time of the lamp | 50,000 hrs |
| Colour temperature | 3000/4200/6000K |
| Number of switching cycles before premature lamp failure | ≥15,000 |
| Warm-up time up to 60% of the full light output | Instant full light |
| Dimmable | No |
| Nominal beam angle | 120° |
| Rated power | 14W |
| Rated lamp lifetime | 50,000 hrs |
| Displacement factor | ≥0.8 |
| Lumen maintenance factor at end of nominal life | ≥0.8 |
| Starting time | Instant full light |
| Colour rendering | ≥80 Ra |
| Colour consistency | Within 6 step Macadam ellipse |
| Rated peak intensity | 445cd |
| Rated beam angle | 120° |
| Voltage / Frequency | 240V~50Hz |
| Lumen efficacy: 111/119/114 lm / W | |
| This product contains a Light Source of Energy Efficiency Class E | |
| Not suitable for accent lighting | |

COLOUR TEMPERATURE SELECTABLE
CIRCULAR 14W LED CEILING/WALL LIGHTS

- Polycarbonate diffuser
- Hinged LED array • Push fit terminal block
- All fittings come with a white full trim
- Colour temperature selectable - options of 3000K, 4200K & 6000K easily set by a dip switch on the driver
- Enclosure rated as IK10 for impact resistance
- Central BESA box mounting option on the base



LiFePO4 EMERGENCY VERSIONS:

- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Battery - LiFePO4 3.2V 1500mAh
- Battery 5 year warranty - Replacement battery code: EB11

MICROWAVE SENSOR VERSION:

- Rated Load - 800W (resistive), 400W (inductive), 270W (LED)
- Adjustable detection angle: up to 150°
- Power consumption: <0.5W
- Adjustable detection range: Max. 6m
- Adjustable time setting: 5 seconds - 30 minutes
- Adjustable Lux control: 2-50 lux
- Push connect terminals: for ease of connection

All fittings come with a white full trim - other trims available

| Code | Version | Wattage | Colour Temp. | Lumens | Avg. Rated Life (Hrs) | IP / IK Rating | MOM / OPQ |
|------------|-------------------|---------|-------------------------|-------------------------------|-----------------------|----------------|-----------|
| KCIRSTD | Standard | 14W | 3000K 4200K 6000K | 1560 lm 1670 lm 1600 lm | 50,000 hrs | IP65 IK10 | 1 / 10 |
| KCIRMW | MW | | | | | | |
| KCIREM3 | EM3 | | | | | | |
| KCIRMW3 | MW + EM3 | | | | | | |
| KCIREYEBK | Black Eyelid Trim | | | | | | 1 / 1 |
| KCIREYEGY | Grey Eyelid Trim | | | | | | |
| KCIREYEWB | White Eyelid Trim | | | | | | |
| KCIRFULLBK | Black Full Trim | | | | | | |
| KCIRFULLCR | Chrome Full Trim | | | | | | |



5
Year Warranty



Emergency
Product



LiFePO4 Battery



IP65



IK10



Colour Temp.
Selectable



Microwave
Sensor



IES Files



Double
Insulated



BESA Box
Compatible