



**Eterna**<sup>®</sup>  
Everyday Lighting For Professionals




LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser): <b>Warm White, Cool White, Daylight White</b>	<b>1560 lm</b> <b>1670 lm</b> <b>1600 lm</b>
Lumens from chip (array): <b>Warm White, Cool White, Daylight White</b>	<b>1760 lm</b> <b>1880 lm</b> <b>1800 lm</b>
Useful lumens (array): <b>Warm White, Cool White, Daylight White</b>	<b>1400 lm</b> <b>1500 lm</b> <b>1440 lm</b>
Rated Wattage	14W
Rated luminous flux	1400/1500/1440 lm
Nominal life time of the lamp	50,000 hrs
Colour temperature	3000/4200/6000K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	120°
Rated power	14W
Rated lamp lifetime	50,000 hrs
Displacement factor	≥0.8
Lumen maintenance factor at end of nominal life	≥0.8
Starting time	Instant full light
Colour rendering	≥80 Ra
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	445cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Lumen efficacy: 111/119/114 lm / W	
This product contains a Light Source of Energy Efficiency Class E	
Not suitable for accent lighting	

- LED
- 5 Year Warranty
- Emergency Product
- Li-Ion Battery
- IP65
- IK10
- Colour Temp. Selectable
- Microwave Sensor
- ✓ IES Files
- Double Insulated
- BESA Box Compatible

**COLOUR TEMPERATURE SELECTABLE CIRCULAR 14W LED CEILING/WALL LIGHTS**

- Polycarbonate diffuser
- Hinged LED array • Push fit terminal block
- All fittings come with a white full trim
- Colour temperature selectable - options of 3000K, 4200K & 6000K easily set by a dip switch on the driver
- Enclosure rated as IK10 for impact resistance
- Central BESA box mounting option on the base



**LI-ION EMERGENCY VERSIONS:**

- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Battery - Li-Ion 3.2V 1500mAh • Battery 1 year warranty - Replacement battery code: EB11

**MICROWAVE SENSOR VERSION:**

- Rated Load - 800W (resistive), 400W (inductive), 270W (LED)
- Adjustable detection angle: up to 150°
- Power consumption: <0.5W
- Adjustable detection range: Max. 6m
- Adjustable time setting: 5 seconds - 30 minutes
- Adjustable Lux control: 2-50 lux
- Push connect terminals: for ease of connection

Code	Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
KCIRSTD	Standard	14W	3000K 4200K 6000K	1560 lm 1670 lm 1600 lm	50,000 hrs	IP65 IK10	1 / 10
KCIRMW	MW						
KCIREM3	EM3						
KCIRMW3	MW + EM3						
KCIREYEBK	Black Eyelid Trim	1 / 1					
KCIREYEGY	Grey Eyelid Trim						
KCIREYEWB	White Eyelid Trim						
KCIRFULLBK	Black Full Trim						
KCIRFULLCR	Chrome Full Trim						

