

5
Year Warranty



Double Insulated




Hole Knockouts

10W LED BULKHEAD WITH OPAL DIFFUSER & PHOTOCELL OPTION

Highly efficient 104 lm/W, super bright general purpose bulkhead

- Tough polycarbonate construction
- Three 20mm knock-out conduit entry positions, one each end and one on rear

KRECBOP LPC: Integral photocell: automatic dusk to dawn operation



Code	Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
KRECBOP L	Standard	10W	4000K	1045 lm	40,000 hrs	IP65	1 / 10
KRECBOP LPC	Photocell						

LED LAMP SPECIFICATIONS:

Luminaire lumens (with diffuser)	1045 lm
Lumens from chip (no diffuser)	1215 lm
Useful lumens	965 lm
Rated Wattage	10W
Rated luminous flux	965 lm
Nominal life time of the lamp	40,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	>15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	120°
Rated power	10W
Rated lamp lifetime	40,000 hrs
Displacement factor	0.93
Lumen maintenance factor at end of nominal life	>0.9
Starting time	Instant full light
Colour rendering	>80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	255cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz

Lumen efficacy: 104 lm / W

This product contains a Light Source of Energy Efficiency Class E

Not suitable for accent lighting