


LINKCS RANGE

Colour Temperature Selectable Undercabinet Linkable Strip Lights




Extend with a link lead accessory

2 EASY LINKABLE OPTIONS

Create a continuous light line by clicking together

INCLUDED: mains cable, 30cm link lead and fixing clips



• Superb light output and distribution, with opal diffuser for a soft effect - perfect for task lighting

• Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)

• Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end

• Simple rocker switch for local on/off control

• Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required)


• Slimline design for unobtrusive installation under cabinets. Ideal for kitchens

• 5 year warranty

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating
LINKCS4	4W	3000K 4200K 6500K	380 lm 385 lm 390 lm	25,000 hrs	IP20
LINKCS9	9W	3000K 4200K 6500K	896 lm 901 lm 905 lm		
LINKCS13	13W	3000K 4200K 6500K	1264 lm 1280 lm 1295 lm		
LINKL05	Optional 50cm link lead				

LINKCS RANGE

Colour Temperature Selectable Undercabinet Linkable Strip Lights




Extend with a link lead accessory

2 EASY LINKABLE OPTIONS

Create a continuous light line by clicking together

INCLUDED: mains cable, 30cm link lead and fixing clips



• Superb light output and distribution, with opal diffuser for a soft effect - perfect for task lighting

• Link a maximum of 12 fittings end-to-end for a continuous line, or space apart with the 30cm link lead (included)

• Safe and simple connectivity thanks to the dual polarity of the 2 pins at each end

• Simple rocker switch for local on/off control

• Fitting comes with a 1.8m mains lead, 30cm link lead, and integral plug & sockets for simple and easy connection (no driver required)

• Slimline design for unobtrusive installation under cabinets. Ideal for kitchens

• 5 year warranty

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating
LINKCS4	4W	3000K 4200K 6500K	380 lm 385 lm 390 lm	25,000 hrs	IP20
LINKCS9	9W	3000K 4200K 6500K	896 lm 901 lm 905 lm		
LINKCS13	13W	3000K 4200K 6500K	1264 lm 1280 lm 1295 lm		
LINKL05	Optional 50cm link lead				