



illumination, gardens and porches, staircases and many more.

- Polycarbonate construction
- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output
- Instant start to full illumination level
- Stainless steel screws
- 4200K colour temperature: for bright neutral white
- IP66 ceiling or wall mounted: giving versatile fixing options suitable for bathroom, internal and external use
- M.O.M: 1 / O.P.Q: 10






Code	Diffuser	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	UK Energy Rating
MINIFULLBK	Standard	Black	6W	4200K	380 lm	35,000 hrs	IP66	A+
MINIFULLWH		White						
MINIEYEBK	Eyelid	Black			330 lm			А
MINIEYEWH		White						



Discrete range of robustly constructed amenity lights offering reliability, style and performance for open access areas.

MINIFULL



LAMP SPECIFICATIONS:	MINIFULL	MINIEYE		
Lumens total flux	380 lm	330 lm		
Lumens 120° flux	340 lm	300 lm		
Rated Wattage	6W	6W		
Rated luminous flux	380 lm	330 lm		
Nominal life time of the lamp	35,000 hrs	35,000 hrs		
Colour temperature	4200K	4200K		
Number of switching cycles before premature lamp failure	≥15,000	≥15,000		
Warm-up time up to 60 % of the full light output	Instant full light	Instant full light		
Dimmable	No	No		
LED array dimensions	Ø: 150mm	L: 150 x H: 115mm		
Nominal beam angle	120°	120°		
Rated power	6W	6W		
Rated lamp lifetime	35,000 hrs	35,000 hrs		
Lamp power factor	>0.8	>0.8		
Lumen maintenance factor at end of nominal life	≥0.70	≥0.70		
Starting time	<0.1s	<0.1s		
Colour rendering	≥80	≥80		
Colour consistency	Within 6 step Macadam ellipse	Within 6 step Macadam ellipse		
Rated peak intensity	140cd	120cd		
Rated beam angle	120°	120°		
Voltage	240V	240V		
Not suitab	le for accent lighting			