




Night view of illuminated strip



- 1** Year Warranty
- IP44
- Bathroom Zone 2
- Earthed

Eterna[®]
Everyday Lighting For Professionals

LAMP SPECIFICATIONS:

Nominal Wattage	15W
Rated Wattage	15W
Average lifetime hours	15,000 hrs
Nominal useful luminous flux	1010 lm
Rated luminous flux	1010 lm
Luminous efficacy (Lm/W) in 50Hz operation	67
Luminous efficacy (Lm/W) in HF operation	67
Rated lamp Lumen maintenance	2000hrs: 95%
	4000 hrs: 92%
	6000 hrs: 91%
	8000 hrs: 91%
	12000 hrs: 85%
Rated survival factors	2000hrs: 99%
	4000 hrs: 97%
	6000 hrs: 95%
	8000 hrs: 91%
	12000 hrs: 85%
Lamp dimensions (mm)	450mm
Cap type	G13
Lamp Mercury content to an accuracy of 0.1mg	≤2.5mg
Colour rendering index Ra	≥80
Colour temperature	2700K
Ambient temperature required to achieve maximum luminous flux	25°C
Dimmable	No
Ballast EEL	A2



IP44 MIRROR LIGHT WITH DUAL VOLTAGE SHAVER SOCKET

- Requires 2 x 15W G13 T8 450mm fluorescent tubes (included). Fitting is rated at 15W max (per lampholder)
- Pull cord on/off switch
- Diffused rectangular light apertures: soft lighting effect
- Permanent power to integrated dual voltage shaver socket: eliminates the need for separate shaver socket
- Safety isolating transformer on shaver outlet: suitable for bathroom use
- High frequency electronic ballast: instant start, flicker free operation, and prolonged lamp life
- Please note: bathroom shaver lights are not suitable for toothbrush chargers

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
ML5040	2 x 15W	2700K	2 x 1010 lm	15,000 hrs	IP44	1 / 1