



Clip on cover



Back of fitting




LED RECESSED WALL LIGHT

Ideal for low level lighting in plinths, stairways etc

- Polycarbonate construction
 - 4000K colour temperature: offering a pleasing lighting effect
 - Instant start to full illumination level
 - Built in driver electronics: connects direct to AC mains
 - Compact design: designed for mounting in a 1 gang 35mm or 47mm deep socket box
 - Eterna 2 year warranty
- M.O.M: 1 / O.P.Q: 100



Code	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	Energy Rating
RWL15	White	1.5W	4000K	96 lm	30,000 hrs	A+



Eterna RWL15

This luminaire contains built-in LED lamps.

A++
A+
A
B
C
D
E } **LED**

The lamps cannot be changed in the luminaire.

874/2012

LED LAMP SPECIFICATIONS:

Lumens total flux	96 lm
Lumens 120° flux	90 lm
Rated Wattage	1.5W
Rated luminous flux	96 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
LED array area (L/W)	63x25mm
Nominal beam angle	120°
Rated power	1.5W
Rated lamp lifetime	30,000 hrs
Lamp power factor	0.8
Lumen maintenance factor at end of nominal life	70%
Starting time	<0.5s
Colour rendering	>80 Ra
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	29cd
Rated beam angle	120°
Voltage	240V

Not suitable for accent lighting

