		hting design ser	vice available	
		LED LAMP SPECIFICATIONS:		
	Luminaire lumens (with diffuser)	437 lm		
	Lumens from chip (no diffuser)	470 lm	5	
	Useful lumens	409 lm	Year Warranty	
	Rated Wattage	4.5W		
	Nominal life time of the lamp	50,000 hrs	Emergency Product	
	Colour temperature	6000K	Product	
	Voltage / Frequency	220-240V~50Hz		
	Ambient Temp	-20 - 45°C		
			Self-Test Emergency	
			IK08	
(11) (11)			Li-ion Battery	
			✓ IES Files	
			Double Insulated	
1111				
FL	- 3	10	Hole	
		7/	Knockouts	
8				
Charge 🝙		C	arg <sup>a</sup> 🚱	
Charge 🕥 Fault 🕥		F	ault 🚳	
Fault 🕥				
			(G)	


**Eterna**<sup>®</sup> Everyday Lighting For Professionals

## SELF-TEST LI-ION EMERGENCY LED TWINSPOT

A flexible emergency light fitting which provides peace of mind thanks to long-lifetime, replaceable li-ion batteries, built-in automatic self-test functionality, durable product construction and long product warranty perfect for commercial and industrial indoor applications

- Twin 4.5W individually rotatable LED projectors for widespread illumination in emergency operation
- Horizontally and vertically adjustable heads, with 180° rotation across the horizontal plane
- Individual indicator LEDs show 'healthy battery charge' or 'fault' status
- Replaceable long-life lithium-ion batteries; minimum 3 hour non-maintained functionality in emergency mode
- 3.2V Li-ion 4500mAh Battery 1 year warranty Replacement battery code: EB18
- Automatic Testing complies with EN 62034
- Durable polycarbonate construction rated to IK08
- Push fit terminals
- 5 year product warranty

Code	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
SETSPOT	4.5W	6000K	437 lm	50,000 hrs	IP20 / IK08	1 / 20



3