



**5**  
Year Warranty




**Eterna**<sup>®</sup>  
Everyday Lighting For Professionals

**LED AMENITY CEILING / WALL LIGHTS**

Long life, energy efficient utility fitting perfect for domestic or commercial settings including perimeter lighting, paths, gardens and porches, communal areas, staircases and many more

- Polycarbonate / ABS construction
- Stainless steel screws
- IP66 ceiling or wall mounted
- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output
- 4200K colour temperature: for bright neutral white appearance



Code	Colour	Diffuser	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
<b>Standard</b>								
SHFULLBK	Black	Full	12W	4200K	800 lm	25,000 hrs	IP66 IK08	1 / 10
SHFULLWH	White							
SHEYEBK	Black	Eyelid	12W	4200K	800 lm	25,000 hrs	IP66 IK08	1 / 10
SHEYEWH	White							
<b>Microwave</b>								
SHFULLMWBK	Black	Full	12W	4200K	800 lm	25,000 hrs	IP66 IK08	1 / 10
SHFULLMWWH	White							
SHEYEMWBK	Black	Eyelid	12W	4200K	800 lm	25,000 hrs	IP66 IK08	1 / 10

LAMP SPECIFICATIONS:	SHFULL	SHEYE
Lumens total flux	<b>800 lm</b>	<b>800 lm</b>
Lumens 120° flux	<b>730 lm</b>	<b>730 lm</b>
Rated Wattage	12W	12W
Rated luminous flux	730 lm	730 lm
Nominal life time of the lamp	25,000 hrs	25,000 hrs
Colour temperature	4200K	4200K
Number of switching cycles before premature lamp failure	>15,000	>15,000
Warm-up time up to 60 % of the full light output	Instant full light	Instant full light
Dimmable	No	No
Lamp dimensions	Ø 140mm	L: 180 x H: 77mm
Nominal beam angle	120°	120°
Rated power	12W	12W
Rated lamp lifetime	25,000 hrs	25,000 hrs
Lamp power factor	>0.93	>0.93
Lumen maintenance factor at end of nominal life	≥70%	≥70%
Starting time	<0.1s	<0.1s
Colour rendering	≥80%	≥80%
Colour consistency	Within 6 step Macadam ellipse	Within 6 step Macadam ellipse
Rated peak intensity	480cd	480cd
Rated beam angle	120°	120°

Not suitable for accent lighting