

SURFACE MOUNTED - NO NEED TO CREATE A RECESS!




Eterna
Everyday Lighting For Professionals



LED SLIM SURFACE FITTING

Superslim surface mounting mains voltage LED amenity fixtures for garden and path illumination, which offers a fantastic alternative to traditional bricklights without the hassle of recessed installation

- ABS housing, polycarbonate diffuser



Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
SLICELONG	3W	4000K	188 lm	30,000 hrs	IP65	1 / 24
TRIMLONG	White Trim					

LED LAMP SPECIFICATIONS:	SLICELONG
Lumens total flux	188 lm
Lumens 120° flux	175 lm
Rated Wattage	3W
Rated luminous flux	188 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	4000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
LED array dimensions (L/W)	175 x 35mm
Nominal beam angle	120°
Rated power	3W
Rated lamp lifetime	30,000 hrs
Lumen maintenance factor at end of nominal life	70%
Starting time	<0.5s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	56.4cd
Rated beam angle	120°
Voltage	240V
Not suitable for accent lighting	



5
Year Warranty

