## Lighting design service available



	LED LAMP SPECIFICATION	IS:	
	Luminaire lumens (with diffuser)	240 lm	
	Lumens from chip (no diffuser)	370 lm	
	Useful lumens	220 lm	
	Rated Wattage	4.3W	
1	Rated luminous flux	220 lm	
	Nominal life time of the lamp	30,000 hrs	
	Colour temperature	4000K	
	Number of switching cycles before premature lamp failure	15,000	
	Warm-up time up to 60% of the full light output	Instant full light	
1	Dimmable	No	
	Nominal beam angle	120°	
	Rated power	4.3W	
	Rated lamp lifetime	30,000 hrs	
	Lamp power factor	>0.4	
1	Lumen maintenance factor at end of nominal life	>0.7	
	Starting time	<0.5	
	Colour rendering	>80	
	Colour consistency	Within a six step Macadam ellipse	
	Rated peak intensity	76cd	
	Rated beam angle	120°	

Voltage / Frequency

Not suitable for accent lighting

240V~50Hz

Fully adjustable head


## **Eterna** Everyday Lighting For Professionals

## **ALUMINIUM LED WALL SPOT LIGHT**

Aluminium construction & frosted glass lens

Integrated driver and LED light source

• Fully adjustable head



Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
SPOTLEDWAL	4.3W	4000K	240 lm	30,000 hrs	IP44	1/12

i	130mm	
85mm		

1	-1	_	1	
1	1			