




**5**  
Year Warranty



**PLASTIC LED UNDER CABINET LIGHT**

- Polycarbonate construction
- 3000K warm white colour temperature: offering a pleasing lighting appearance
- 2W = 100 lumens: ideal low energy solution to standard halogen cabinet lights
- Pre-wired with 2m mains cable and no separate driver required: facilitating easy installation
- Not suitable for use with dimmers
- Not suitable for recessed installation



**LED LAMP SPECIFICATIONS:**

Luminaire lumens (with diffuser)	<b>100 lm</b>
Lumens from chip (no diffuser)	<b>150 lm</b>
Useful lumens	<b>100 lm</b>
Rated Wattage	2W
Rated luminous flux	100 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	3000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	90°
Rated power	2W
Rated lamp lifetime	30,000 hrs
Lamp power factor	>0.5
Lumen maintenance factor at end of nominal life	70
Starting time	<0.5s
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	55.97cd
Rated beam angle	90°
Voltage / Frequency	240V~50Hz
Not suitable for accent lighting	

Code	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
VECOABPTR	2W	3000K	100 lm	30,000 hrs	IP20	1 / 100