Eterna	VECOCSBAT5
This luminaire contains built-in LED lamps.	
A ⁺ A C D	}L E D
The lamps cannot be changed in the luminaire.	
874/2012	0

LED LAMP SPECIFICATIONS:		
Luminaire lumens (with diffuser): Warm White, Cool White, Daylight White	5000 lm 5900 lm 5350 lm	
Lumens from chip (array): Warm White, Cool White, Daylight White	7150 lm 7850 lm 7450 lm	
Useful lumens (array): Warm White, Cool White, Daylight White	4650 lm 5450 lm 5000 lm	
Rated Wattage	58W	
Rated luminous flux	4650/5450/5000 lm	
Nominal life time of the lamp	30,000 hrs	
Colour temperature	3000/4000/6800K	
Number of switching cycles before premature lamp failure	>15,000	
Warm-up time up to 60% of the full light output	Instant full light	
Dimmable	No	
Nominal beam angle	120°	
Rated power	58W	
Rated lamp lifetime	30,000 hrs	
Lamp power factor	>0.9	
Lumen maintenance factor at end of nominal life	>0.7	
Starting time	0.1s	
Colour rendering	>80	
Colour consistency	Within 6 step Macadam ellipse	
Rated peak intensity	1743cd	
Rated beam angle	120°	
Voltage / Frequency	240V~50Hz	
Not suitable for accent lighting		





INSTALLATION INSTRUCTIONS

A guide for qualified electricians

Pack contents: 1 x LED batten

Model:

VECOCSBAT5

Colour Temperature Selectable 5ft Batten

These instructions are provided as a guideline to assist you.

PLEASE READ THESE INSTRUCTIONS BEFORE INSTALLATION AND RETAIN FOR FUTURE REFERENCE

READ THIS FIRST:

Check the pack and make sure you have all of the parts listed on the front of this booklet. If not, contact the outlet where you bought this product.

This product must be installed by a competent person in accordance with the current building and IEE wiring regulations.

As the buyer, installer and/or user of this product it is your own responsibility to ensure that this fitting is fit for the purpose for which you have intended it. Eterna Lighting cannot accept any liability for loss, damage or premature failure resulting from inappropriate use.

This product is designed and constructed according to the principles of the appropriate British Standard and is intended for normal service. Using this fitting in any other environments may result in a shortened working life, for example where there is prolonged periods of use or higher than normal ambient temperatures.

Switch off the mains before commencing installation and remove the appropriate circuit fuse or lock off MCB.

Disconnect from the electrical supply before flash or high voltage testing.

Do not connect to a circuit which also has inductive loads connected; switching of inductive loads will generate spikes which may damage electronic components within your driver.

This unit is suitable for indoor use only.

This product is designed for permanent connection to fixed wiring: this must be a suitable circuit (protected with the appropriate MCB or fuse).

Before making fixing hole(s), check that there are no obstructions hidden beneath the mounting surface such as pipes or cables.

Make sure that the fixings are strong enough to support the considerable weight of the fitting and hold it rigidly.

The chosen location of your new fitting should allow for the product to be securely mounted (e.g. to a ceiling joist) and safely connected to the mains supply (lighting circuit).

This product must be connected to earth termination.

This product is not intended to be used by children and persons with sensory, physical and/or mental impairments that would prevent them from using it safely.

You are advised at every stage of your installation to double-check any electrical connections you have made. After you have completed your installation there are electrical tests that should be carried out, these tests are specified in the current IEE wiring and building regulations.

LAMP REPLACEMENT:

The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.

EVENTUALLY, YOU MAY WANT TO REPLACE THIS PRODUCT:

Regulations require the recycling of Waste from Electrical and Electronic Equipment (European "WEEE Directive" effective August 2005—UK WEEE Regulations effective 2nd January 2007). Environment Agency Registered Producer: WEE/GA0248QZ.

WHEN YOUR PRODUCT COMES TO THE END OF ITS LIFE OR YOU CHOOSE TO REPLACE IT, PLEASE RECYCLE IT WHERE FACILITIES EXIST - DO NOT DISPOSE WITH HOUSEHOLD WASTE.

CLEANING:

Disconnect the power and clean the exterior only of this fitting with a moist (not wet) cloth.

Do not use any chemical or abrasive cleaners.

IF YOU EXPERIENCE PROBLEMS:

If you believe your product is defective, please return it to the place where you bought it. Our Technical Team will gladly advise on any Eterna Lighting product, but may not be able to give specific instructions regarding individual installations.

INSTALLATION:

- 01) Choose the location of your new fitting giving consideration to all of the conditions listed above and the position of the entry points for the mains supply cable.
- 02) Using the fitting and fixing clips as a template, mark the location of the fixing holes on your mounting surface.
- 03) Secure the fixing clips to the mounting surface.
- 04) Connect mains supply cable to plug connector according to the following colour code, ensuring polarity is observed:

Live - Brown or Red Neutral - Blue or Black Earth - Green and Yellow

NOTE: once connections are made to the plug connector, it is NOT possible to remove the cable. Take care to ensure connections are correct.

- 05) Set colour temperature to the desired option using the external switch, selecting between 3000K, 4000K and 6800K.
- 06) Connect both sides of the plug connector and ensure this is securely fixed.
- 07) Clip the fitting to the fixing clips on the mounting surface.
- 08) Restore the power supply and switch on.