






**Eterna**®

## **10W ECONOMY LED BULKHEAD**

- Polycarbonate diffuser, polycarbonate /

- 5 year warranty
- M.O.M: 1 / O.P.Q: 12



65mm 120mm

Avg. Rated Colour Luminaire Wattage Code Colour Life (Hrs) Rating Temp. Lumens **VECOPIRBH** Black 10W 4000K 700 lm 25,000 hrs IP54

| LED LAMP SPECIFICATIONS:                                 |                                      |
|--|--------------------------------------|
| Luminaire lumens (with diffuser)                         | 700 lm                               |
| Lumens from chip (no diffuser)                           | 900 lm                               |
| Useful lumens  | 650 lm                               |
| Rated Wattage  | 10W                                  |
| Rated luminous flux                                      | 650 lm                               |
| Nominal life time of the lamp                            | 25,000 hrs                           |
| Colour temperature                                       | 4000K                                |
| Number of switching cycles before premature lamp failure | 15,000                               |
| Warm-up time up to 60% of the full light output          | Instant full light                   |
| Dimmable   | No                                   |
| Nominal beam angle                                       | 120°                                 |
| Rated power  | 10W                                  |
| Rated lamp lifetime                                      | 25,000 hrs                           |
| Displacement factor                                      | 0.94                                 |
| Lumen maintenance factor at end of nominal life          | 70%                                  |
| Starting time  | 0.5s                                 |
| Colour rendering   | 80                                   |
| Colour consistency                                       | Within a six step<br>Macadam ellipse |
| Rated peak intensity                                     | 208cd                                |
| Rated beam angle   | 120°                                 |
| Voltage / Frequency                                      | 220-240V~50/60Hz                     |
| This product contains a Light Source of Energy           |                                      |

Efficiency Class E

Not suitable for accent lighting