





LED COLOUR TEMPERATURE SELECTABLE SLIM WALL PACK

Slim profile, durable and high performance colour selectable wall pack offering reliability for outdoor utility applications

- Colour temperature selectable - options of 3000K, 4000K & 6000K easily set by a dip switch on the driver • Up to 90 lm/W
- ABS base and polycarbonate diffuser • Slim design
- Opal diffuser: evenly diffused light output
- 20mm cable entries on either side and one to the rear

PHOTOCELL VERSIONS: Photocell for dusk to dawn operation

Code	Colour	Version	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
WPCSBK	Black	Standard	17W	3000K	1500 lm	36,000 hrs	IP65	1 / 10
WPCSWH	White			4000K	1550 lm			
WPCSBKPC	Black	Photocell		6000K	1530 lm			
WPCSWHPC	White							



LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser): Warm White, Cool White, Daylight White	1500 lm 1550 lm 1530 lm
Lumens from chip (array): Warm White, Cool White, Daylight White	1750 lm 1850 lm 1850 lm
Useful lumens (array): Warm White, Cool White, Daylight White	1450 lm 1500 lm 1480 lm
Rated Wattage	17W
Rated luminous flux	1450/1500/1480 lm
Nominal life time of the lamp	36,000 hrs
Colour temperature	3000/4000/6000K
Number of switching cycles before premature lamp failure	15,000
Warm-up time up to 60% of the full light output	<1s
Dimmable	No
Nominal beam angle	120°
Rated power	17W
Rated lamp lifetime	36,000 hrs
Lamp power factor	>0.9
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	360cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Not suitable for accent lighting	



5  
Year Warranty



K  
Colour Temp.  
Selectable

