

Type of Light source

| | |
|---|-----------------|
| Lighting Technology used | LED |
| Non-Directional or Directional | Non Directional |
| Light Source Cap type (or other interface) | N/A |
| Mains or non-mains | Mains |
| Connected Light source (CLS) | No |
| Colour tuneable light source | No |
| High Luminance Light source | No |
| Anti Glare shield | No |
| Dimmable (Dimmers listed in Product File if applicable) | No |

Product Parameters

| | |
|---|--------------|
| Energy consumption kW/1000hrs (enter wattage / On Mode Power) | 18 |
| Energy Efficiency Class | E |
| Useful Luminous Flux (lumens) | 2299 |
| Beam angle correspondence | Wide Cone |
| Correlated Colour temperature | Single value |
| Correlated Colour temperature (K) | 4000 |
| On-mode Power (W) | 18 |
| Standby Power | 0 |
| Networked Standby Power | 0 |
| Colour Rendering Index | 83 |
| Colour Rendering Index Range | |
| Dimensions Height | 67 |
| Dimensions width | 58 |
| Dimensions depth | 1185 |
| Chromaticity coordinates x | 0.377 |
| Chromaticity coordinates y | 0.376 |

Parameters for Directional Light Sources

| | |
|------------------------------------|-----|
| Peak Luminous Intensity (cd) | N/A |
| Beam Angle (degrees) | 120 |
| Beam Angle range minimum (degrees) | |
| Beam Angle range maximum (degrees) | |

Parameters for Led & OLED sources

| | |
|----------------------------|-----|
| R9 Colour rendering Index | 10 |
| Survival Factor | 0.9 |
| Lumens maintainance factor | 0.8 |

Parameters for Led & OLED mains sources

| | |
|--|--------|
| Displacement Factor | 0.95 |
| Colour Consistency in SDCM Steps | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage Replacement claim (W) | N/A |
| Flicker Metric Pst | 0.003 |
| Stroboscopic Effect Metric SVM | 0.363 |
| Spectrum Report available | Yes |
| EPREL Registration | 765557 |